



LYNX SERIES



LYNX 32



Full color crystal clear LED screen

- Capacity pump 008 m³/h
- Machine cycle 15-30 sec.
- Dimensions (L x W x H) 534 x 400 x 385 mm
- Weight 35 kg
- Voltage 230V-1-50 Hz (other voltages available)
- Power 0,5 kW

Pure Vacuum

LYNX SERIES

INNOVATIVE AND INTELLIGENT VACUUM PACKAGING MACHINES WITH WORLD WIDE REPUTATION

- High quality compact table models
- Pure and attractive Design
- Intelligent full colour Control Interface
- Extensive packaging parameters for specific packaging requirements
- Full HACCP compatible with labelling device
- Easy clean concept

FOOD PRODUCTS

Retail Trade - Restaurants - Catering - Supermarkets
(meat, poultry, fish, cheese, vegetables etc.)

- No contamination or bacteria's multiplication, hence an extended shelf life resulting in:
 - cost savings (larger purchasing orders, efficient cooking time spreading and diminution of products losses)
 - turnover increase (more variation and spread in product range)
- Optimal product and storage hygiene (hermetically sealed)
- No loss of product (prevents drying out, moulds and freeze burn)
- Improved product quality (product maturing in packaging, no loss of aroma)
- Professional product presentation
- Optimal packaging contributes to food safety and HACCP standards
- Ideal for Sous-vide Cuisine applications

NON-FOOD PRODUCTS

Electronics - Semi-conductors - Metal - Pharmaceutical Products -
Textiles - Laboratories etc.

- Moisture free packaging
- Air and dust free packaging
- Volume reducing packaging
- Scrapes and scratches free solution
- Fraud resistant packaging
- Sterile and contamination free packaging



SPECIFICATIONS

GENERAL

- Compact Table top model
- Innovative Intelligent Design
- High volume transparent lid
- Easy clean flat working plate
- Removable wireless sealing bars
- Insert plates for fast cycle and product adjustment
- Full colour wide screen
- User friendly interface
- 6 languages operational mode
- 20 programs adjustable in % and mbar/ hPa
- USB port for data transfer
- Printing and Labelling function
- Service data storage
- Program access security
- In compliance with HACCP regulations

PACKAGING FUNCTIONS

- **Vacuum**
Optimal final vacuum 99,80% (2 mbar)
- **Gas-flush**
Injecting food-gas for product protection and longer shelf life
- **Soft-air**
Controlled ventilation for protection of product and packaging

SEALING SYSTEMS

- **Double Seal**
2 x 3,5 mm convex sealing wires for product remains elimination and strong hermetic seals.
- **Cut-off seal**
1 x 3,5 mm convex sealing wire + 1 x 1.1 mm round cutting wire / One time setting (cut off remaining flap)
- **1-2 Cut-off seal**
1 x 3,5 mm convex sealing wire + 1 x 1.1 mm round cutting wire / Independent time setting (shrink bags)
- **Wide Seal**
1 x 8.0 mm flat sealing wire

CONTROL FUNCTIONS

- **Sensor Control**
Set percentage or pressure for vacuum and gas functions for accurate and constant packaging results / Automatic programming / 20 default programs / Vacuum plus time / Red meat device / Sequential vacuum
- **Quick stop H₂O Sensor Control**
Set percentage pressure for vacuum and detect boiling point of the product. For fast cycle and better food protection
Automatic programming / 20 default programs / Vacuum plus time / Red meat device / Sequential vacuum

SUPPORT CONTROL FUNCTIONS

- STOP button for full cycle interruption
- Digital maintenance program for pump / Operating hours counter / Service indicator program

ACCESSORIES

- Compact label printer (Zebra Technologies)
- Inclined insert plate for packaging liquid products
- Service kit for standard maintenance
- Trolley with shelves and castors



Optional

Standard

Sentence and printing errors reserved